



INSTALLATION INSTRUCTIONS

Part Number YA-1186

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N Filtercharger® seals properly.

INSTALLATION

1. Remove the stock air filter according to the owners manual.
2. Apply the gasket to the base of the Filtercharger® noting that the end radius matches. (Fig. 1)
3. Remove the long screw from the stock hold down plates. (Fig. 2)
Note: The long screw will not be reused.
4. Remove only two screws and one hold down plate.
5. Install the K&N Filtercharger® in the air box. Slip one tab on the air filter under the hold down plate that was not removed.
6. Reinstall the hold down plate and two screws. Securely tighten. (Fig. 3)
NOTE: Do not overtighten as this may strip the threads in the air box.
7. Reinstall the air box cover.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2



Fig. 3